

Visionary II



Visionary II Color Options

CHANGEMAKER



737 White Oak



749 Hickory



774 Willow



794 Ashwood



796 Aspen



797 Driftwood

CLEVER THOUGHT



527 Canopy



573 Skipping Stone



596 Morning Fog

WELL PREPARED



524 Aloe



572 Dew

HIGH ROAD



592 Misted

Visionary II

Visionary II Collection resilient sheet flooring by Aladdin Commercial, features four soft, organic visuals that are textile-inspired along with natural wood grain looks that create a warm and comforting environment. Constructed for light commercial and residential spaces offering excellent performance and durability, including our Enhanced Urethane Finish for superior wear and stain resistance, along with a no-polish option for lower maintenance costs.

Features:

- Heterogeneous Construction
- 6'6" & 13'2" widths
- 20 mil wear layer
- 0.080" (2 mm) overall thickness
- Enhanced Urethane Finish
- Seams can be cold welded or heat welded
- Install with M95.0 or MS-160 Spray Adhesive
- FloorScore® Certified
- 10 Year Light Commercial Warranty
- 25 Year Residential Warranty

Specifications

RESILIENT SHEET	Brand	Aladdin Commercial Hard Surface	Seaming Method	Mohawk Solid Color Heat Weld or Cold Weld
	Collection	Visionary II	Classification	ASTM F - 1303 Type 1, Grade 1, Class A
	Style Name / Number	Changemaker / AH115	Flexibility	ASTM F137 - Passes
		Clever Thought / AH116	Wear Layer Thickness.....	ASTM F410 - Passes
		Well Prepared / AH117	Thickness.....	ASTM F386 - Passes - as specified ±0.005"
		High Road / AH118	Static Load Limit.....	ASTM F970 - Passes, 750 psi Modified
	Construction	Commercial Grade Heterogeneous Resilient Sheet, Non-ortho Phthalate Construction	Coefficient of Friction.....	ASTM C1028 - Passes, 0.53 West, 0.73 Dry
	Wear Layer	20 MIL	Rolling Load.....	ASTM F2753 - No change
	Gauge.....	.080	Residual Indentation.....	ASTM F1914 - Passes, Average less than 8%
	Finish.....	M-Force	Resistance to Chemicals.....	ASTM F925 - Passes, No Change
Colors Available.....	39.37" X 39.17" w/19.69" Drop (Changemaker, Clever Thought) 39.37" X 39.37" (Well Prepared, High Road)	Resistance to Light.....	ASTM F 1515 - ΔE < 8.0	
Roll Size (Min. — Max.).....	50' — 85'	Resistance to Heat.....	ASTM F 1514 - ΔE < 8.0	
Pattern Repeat	6 (Changemaker) 3 (Clever Thought) 2 (Well Prepared) 1 (High Road)	Electrostatic Propensity.....	AATCC 134 - Less than 3.5 kV	
		Critical Radiant Flux.....	ASTM E648 - Meets, Class 1	
		Smoke Density	ASTM E662 - Meets, 450 or less	
		Sustainability Certification	FloorScore® Certified	
		Warranty.....	Limited 10 Year Commercial Limited 10 Year Under Hospital Bed Warranty using M95.0 or M99.0	

Aladdin[™]
COMMERCIAL

Mohawk Industries, Inc. warrants its adhesives for the life of the original installation only when a Mohawk Industries style (product) is installed. Mohawk's floor preparation procedures must be followed to ensure that the substrate has been prepared properly. Failure to use Mohawk Industries adhesives or to follow Mohawk's floor preparation procedures will void all lifetime adhesive warranties. Please contact your local Sales Representative for installation guidelines.

Mohawk is providing this architect folder for the purpose of promoting our commercial business. Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations or other factors. The performance of this product is not affected by such variations. We recommend the use of chair pads on all commercial installations.

For current and complete specifications please call tech support at 888-387-9881 or visit www.AladdinCommercial.com | 800.233.4490

0032C_Mar/2023

Manufactured in the U.S. with domestic and imported materials

