







Sand Dollar Oak 220
Cover: Ida Cirrus Oak 970



Colors (from bottom to top): 870 Harbor Seal Oak, 970 Ida Cirrus Oak, 170 Mako Oak)

Wildwood Preserve Collection

Wildwood Preserve LVT offers the very best in design and performance. It features beautiful wood-inspired patterns in eight top-of-the-industry colors and superior embossing technology to add realistic textural effects, Wildwood Preserve offers a modern and sophisticated design to elevate and “wow” any commercial environment. Complete with the latest in LVT innovation and construction, Wildwood Preserve is offered in 8” x 48” planks to provide maximum coverage and impact.

Features:

- 2mm thickness
- 12 mil wear-layer
- 8” x 48” plank sizes
- 8 best-selling colors
- Low gloss matte finish
- Glue down installation
- Recommended adhesives: M95.0 Resilient Flooring Adhesive, MS160 Spray or M700 Plus Pressure Sensitive Adhesive
- FloorScore Certified
- Limited 10 Year Commercial Warranty
- Limited 25 Year Residential Warranty



Wildwood Preserve LVT 880 & Brilliantly Amazed Tile 521

Maximize design coordination

Needing a few more products to complete your next Wildwood Preserve project? We've got you covered! Aladdin Commercial offers a diverse array of broadloom, carpet tile, and hard surface products intentionally designed to seamlessly coordinate with other Aladdin Commercial offerings.

Brilliantly Amazed Carpet Tile:

- Commerce Tile Collection
- 24" x 24" tile
- ColorStrand SD Nylon fiber for long-lasting color
- UltraSet Matrix backing
- 7 colors that coordinate well with Wildwood Preserve LVT offerings
- Provides a modern, geometric aesthetic that ties well with Wildwood Preserve natural wood-inspired patterns
- Monolithic, Multi-Directional, Brick Ashlar, and Vertical Ashlar installations available

Enduring Function Broadloom:

- Inspiration Collection
- Broadloom
- ColorStrand SD Nylon fiber for long-lasting color
- Weldlok Plus backing
- 7 colors that coordinate well with Wildwood Preserve LVT offerings
- Contains intricate random square patterns designed to add calmness and personality to any commercial environment and pairs well with Wildwood Preserve natural wood-inspired patterns



Brilliantly Amazed Tile 521,
Enduring Function BL 521,
Wildwood Preserve LVT 880, 170, 970

TRIM

Tailored Trim

Complete your next Wildwood Preserve project with our full range of accessory options from our Tailored Trim Collection! Connect with your Aladdin Commercial representative today to discover how Tailored Trim can help you complete your next install.



ADHESIVE

M700 Plus

Take advantage of our ground-breaking cross-platform M700 Plus adhesive. Having the ability to install carpet tile and hard surface product offerings, M700 Plus can reduce the number of adhesives needed on a project, all while delivering top performance and durability. Available to order under A700P.



Colorways for Wildwood Preserve Collection



170 Mako Oak



220 Sand Dollar Oak



370 Nautica Piling



870 Harbor Seal Oak



880 Loggerhead Oak



910 Sea Spray Oak



970 Ida Cirrus Oak



977 Old Onyx Oak

Specifications

LUXURY VINYL TILE	Brand.....	Aladdin Commercial
	Style Name / Number	Wildwood Preserve / AH105
	Product Type	Luxury Vinyl Tile
	Overall Gauge.....	2 mm
	Wear Layer	12 mil
	Finish	Low Gloss Matte
	Colors Available.....	8
	Size	8" X 48"
	Packaging	16 pc/ctn
	SF/Carton	42.72 sf/ctn
	Cartons/Pallet.....	72 ctn/plt
	Weight/Carton.....	27.97 lbs/ctn
	Emboss	SGRL (Roughwood)
	Bevel.....	Squared
	Classification	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
	Squareness.....	ASTM F 2421 - Passes - $\pm 0.10"$ max
	Size and Tolerance	Tile ASTM F2055; Plank ASTM F2421 - Passes - $\pm 0.016"/$ linear foot
	Thickness.....	ASTM F386 - Passes - as specified $\pm 0.005"$
	Flexibility	ASTM F137 - Passes - 1" mandrel
	Dimensional Stability	ASTM F2199 - Passes - 0.020"/linear foot max
	Static Load Limit	ASTM F970 (modified) - 1500 psi
	Residual Indentation	ASTM F1914 - Passes - Average less than 8% maximum single reading 10%
	Resistance to Chemicals	ASTM F925 - Passes - No more than a slight change in surface dylling, surface attack or staining
	Resistance to Light.....	ASTM F1515 - Passes -E <8
	Resistance to Heat Flux..	ASTM E649 - Class 1 (>0.45 W/cm2)
	Smoke Density.....	ASTM E662 Part A - Less than 450
	Installation Method.....	Glue Down
	Adhesive.....	M95.0 Resilient Flooring Adhesive, MS160 Spray or M700 Plus Pressure Sensitive Adhesive
	Certification.....	FloorScore® Certified
	Warranty	Limited 10 Year Commercial Warranty, Limited 25 Year Residential Warranty

Aladdin[™]
COMMERCIAL

Mohawk Industries, Inc. warrants its adhesives for the life of the original installation only when a Mohawk Industries style (product) is installed. Mohawk's floor preparation procedures must be followed to ensure that the substrate has been prepared properly. Failure to use Mohawk Industries adhesives or to follow Mohawk's floor preparation procedures will void all lifetime adhesive warranties. Please contact your local Sales Representative for installation guidelines.

Mohawk is providing this architect folder for the purpose of promoting our commercial business. Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations or other factors. The performance of this product is not affected by such variations. We recommend the use of chair pads on all commercial installations.

For current and complete specifications please call tech support at 888-387-9881, option 3, or visit www.AladdinCommercial.com | 800.233.4490