



RIPPLE TILE FH64T

Specification

Product Type:	Carpet Tile
Construction:	Tufted
Surface Appearance:	Textured Patterned Cut & Loop
Gauge:	1/10 (39.37 rows per 10 cm)
Tufted Face Weight:	36 oz/yd ² (1,221 g/m ²)
Pile Thickness:	.230" (5.84 mm)
Total Thickness EcoFlex (Air):	.414" (10.51 mm)
Stitches Per Inch:	12.1 (47.64 per 10 cm)
Dye Method:	Precision Dye Injection
Fiber Type:	Colorstrand® Nylon
Stain Release Technology:	EcoSentry Plus Stain Protection
Soil Release Technology:	EcoSentry Soil Protection
Density:	5,634
Weight Density:	202,852
Backing Type:	EcoFlex® Air
Total Weight (EcoFlex Air):	155.0 oz/yd ² (5,255 g/m ²)
Installation Method Planks:	Monolithic / Brick Ashlar / Monolithic Stepping
Installation Method Squares:	Monolithic / Brick Ashlar / Vertical Ashlar
Size:	12" x 36" planks or 24" x 24" squares
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450
Static Propensity:	AATCC-134 Under 3.5 KV
IAQ Green Label Plus:	1256
Warranties:	10 Year Limited Carpet Tile Warranty Lifetime Static

All specifications are subject to normal manufacturing tolerances.

1/25