



Mohawk EnPress®

CARPET TILE ADHESIVE



Features & Benefits

Quick Tack

Aggressive Bond

Superior Shear Strength

Mohawk EnPress® carpet tile pressure sensitive adhesive is specially designed to install Mohawk Group carpet tiles with:

- EcoFlex ONE
- EcoFlex Matrix
- EcoFlex AIR
- EcoFlex NXT

EnPress® pressure sensitive adhesive is nonflammable and has low odor and "zero" calculated VOC's, which makes it ideal for use in schools, healthcare facilities, public buildings, and anywhere odor is a concern.

EnPress® pressure sensitive adhesive is CRI Green Label Plus™ certified. This adhesive is not photochemically reactive as defined by California Rules 102 and 443 and also meets or exceeds VOC emission levels set by California SCAQMD Rule 1168. This adhesive contains MicroSept™ broad spectrum antimicrobial protection.

MOISTURE WARRANTY with Enpress Adhesive:

EcoFlex NXT
95 % RH and 12 pH

EcoFlex ONE and EcoFlex AIR
99% RH and 12 pH

EcoFlex Matrix
95 % RH and 12 pH

SPREAD RATE:

EcoFlex NXT, Matrix, & ONE
140-160 sy per 4 gallons with a 3/8" nap roller

EcoFlex AIR
100-120 sy per 4 gallons with a
1/16"x 1/32" x 1/32" U-Notch Trowel

PACKAGING:

- Available in 4 gallon pails
- 48 pails per pallet