



SHAKA II SY031

Specification

Product Type:	Broadloom
Construction:	Tufted
Surface Appearance:	Textured Patterned Cut & Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Tufted Face Weight:	26 oz/yd ² (882 g/m ²)
Pile Thickness:	.222" (5.64 mm)
Estimated Total Thickness:	.382" (9.70 mm)
Stitches Per Inch:	10.5 (41.34 per 10 cm)
Dye Method:	Precision Dye Injection
Fiber Type:	Colorstrand® Nylon
Stain Release Technology:	EcoSentry Plus Stain Protection
Soil Release Technology:	EcoSentry Soil Protection
Density:	4,216
Weight Density:	109,621
Backing Type:	Weldlok®
Base Pattern Repeat:	18" (W) x 34.1" (L)
Width:	12' width (3.66 m)
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450
Static Propensity:	AATCC-134 Under 3.5 KV
IAQ Green Label Plus:	6678
Warranties:	Lifetime Limited Wear Warranty Lifetime Limited Colorfastness to Light 10 Year Limited Colorfastness to Atmospheric Contaminants 10 Year Stain Warranty Lifetime Static

All specifications are subject to normal manufacturing tolerances.

02/24