



Hot & Heavy II PVC-Free 3.0 mm Resilient Tile Mohawk Group

Final Assembly: Hongseong-gun, South Korea

Life Expectancy: 20 Year(s)

End of Life Options: Take Back Program (ReCover)

Ingredients:

Calcium Carbonate; 1-Propene, polymer with ethene; Magnesium hydroxide; Polyethylene; 1-Butene, polymer with ethene; Polypropylene; 1-Octene, polymer with ethene; 1-Propene polymer with ethene, block; 2-Propenoic acid, 1,6-hexanediyl ester; 2-Propenoic acid, 2-(hydroxymethyl)-2-[[[(1-oxo-2-propenyl)oxy]methyl]-1,3-propanediyl ester; 2-Propenoic acid, monoester with 1,2-propanediol; Aluminum hydroxide; Aluminum Oxide; Ammonium polyphosphate; Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, octadecyl ester; Carbon black; methyl benzoylformate; Octadecanamide, N,N'-1,2-ethanediylbis-; Octadecanoic acid, calcium salt; oxybis(methyl-2,1-ethanediyl) diacrylate; Propanedioic acid, [[3,5-bis(1,1-dimethylethyl) -4-hydroxyphenyl]methyl]butyl-, bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester; Silica, amorphous, fumed, cryst.-free; Talc; Titanium dioxide

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| ☒ LBC Red List Free | % Disclosed: 100% at 100ppm |
| ☐ LBC Red List Approved | VOC Content: Not Applicable |
| ☐ Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

MHK-0042

EXP. 01 OCT 2027

Original Issue Date: 2025