

Hand Tufted Rug – HT450

	Metric	Imperial
Weave Type	Hand Tufted	
Pile Yarn (BS 3655)	100% Pure Wool (New Zealand Origin – Cut Pile)	
Yarn Count	R380/1	1/82
Number of Ends / Insertions	4	
Backing Materials	Primary Backing – Cotton 67% / Polyester 33% Secondary Backing – Cotton, Natural Latex With Fire Retardant Compound.	
Gauge	23 ends/dm	5.8 per inch
Rows	20 ends/dm	5.1 per inch
Tuft Density	460 per sq dm	30 per sq inch
Total Pile Height ISO 1766 (BS 4223)	9.5mm	0.37"
Total Rug Thickness ISO 1765 (BS 4051)	11- 12mm	0.43 - 0.47"
Total Pile Weight ISO 8543 (BS 4223)	2440g per sq m	71.96 oz per sq yd
Total Carpet Weight ISO 8543 (BS 4223)	3620 g per sq m	106.75 oz per sq yd

DYEING METHOD		Skein dyeing with pre-metallised complex dyes.	
COLOUR FASTNESS TO	SHAMPOOING	- BS 1006	Minimum 4 – 5
	RUBBING	- BS EN ISO 105-X12 (BS 1006)	Minimum 4 – 5

Qualifications to Specification

1. There may be slight variation between the actual product and the specification.
2. The figures quoted are for PLAIN COLOURED CARPETS IN CUT PILE ONLY.
3. Carpets with intricate designs or using different construction methods shall have considerable differences.