



Pure Arbor



# Pure Arbor

Pure Arbor is a hard surface LVT collection designed to evoke the calm, effortless beauty of clean, refined wood. With minimal knots and distractions, its “pure” grain aesthetic offers a sense of clarity and simplicity, allowing any space to feel grounded and restorative.

Pairing this understated wood visual with the idea of an “arbor” — a sheltered, peaceful resting place — the collection creates an environment that feels inviting, balanced, and naturally comfortable.





# Pure Arbor GLUE DOWN LVT

## PERFORMANCE

- 5mm overall thickness and 0.5mm commercial wear layer for superior durability
- M-Force™ Ultra finish for stain and wear resistance
- Hard surface LVT collection inspired by clean, refined wood aesthetics
- Creates a sense of clarity, simplicity, and calm in any space
- Combines understated beauty with durable, high-performance flooring construction
- FloorScore® Certified
- Limited 20 Year Commercial Warranty

## COLORWAYS

Straight Lay: 18.42 cm x 121.92 cm

Herringbone: 10.16 cm x 60.96 cm



121 Touch of Sand



712 Featherweight



855 Toasty



933 Off the Ropes



959 Shadow Boxing



992 Ginger Root



Pure Arbor 121 Touch of Sand



## Specifications Pure Arbor (MG9197)

### DESIGN

Product Type	Luxury Vinyl Tile - Flexible
Total Thickness	5 mm
Size	18.42 cm x 121.92 cm
	10.16 cm x 60.96 cm
Wear Layer	0.5 mm
Finish	M-Force™ Urethane
Surface Profile	EIR Emboss
Colors Available	6
Packaging	2.23 m <sup>2</sup> /ctn, 10 pcs/ctn
	1.95 m <sup>2</sup> /ctn, 23 pcs/ctn

### PERFORMANCE

Construction	Commercial Grade Flexible LVT
Installation	Glue Down
Classification	ASTM F1700 - Type B - Embossed
Squareness	ASTM F2421 - ±0.10" max
Size and Tolerance	ASTM F2421 - Passes
Thickness	ASTM F386 - Passes - As Specified ±0.005"
Flexibility	ASTM F137 - Passes
Dimensional Stability	ASTM F2199 - Passes
Static Load Limit	ASTM F970 - Passes, modified at 1500 psi
Residual Indentation	ASTM F1914 - Passes
Resistance to Chemicals	ASTM F925 - Passes
Resistance to Light	ASTM F1515 - Passes
Resistance to Heat	ASTM F1514 - Passes
Critical Radiant Flux	ASTM E648 - Class 1
Smoke Density	ASTM E662 - Less than 450

### SUSTAINABILITY

Certification	FloorScore® Certified
---------------	-----------------------

### SERVICE

Warranty	Commercial Limited 20 Year
----------	----------------------------



Pure Arbor 959 Shadow Boxing, 992 Ginger Root



Mohawk Group



**Mohawk Group**  
Rm 802-809, The Place  
No. 100 Zunyi Road  
Shanghai, China  
200336  
86 21 8026 7000