



FlexLok+ Installation System Mohawk Group

Final Assembly: Suwanee, Georgia, USA

Life Expectancy: 15 Year(s)

End of Life Options: Landfill (100%)

Ingredients:

Polyethylene Terephthalate; 2-Propenoic acid, butyl ester, polymer with 2-ethylhexyl 2-propenoate; Pulp, cellulose; Siloxanes and Silicones, di-Me; Oxirane, 2-methyl-, polymer with oxirane, mono[3-[1,3,3,3-tetramethyl-1-[(trimethylsilyl)oxy]-1-disiloxanyl]propyl] ether; Polyester; Polyvinyl acetate; Castor oil, polymer with TDI

Living Building Challenge Criteria: Compliant

I-13 Red List:

☒ LBC Red List Free

☐ LBC Red List Approved

☐ Declared

% Disclosed: 100% at 100ppm

VOC Content: Not Applicable

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

MHK-0003

EXP. 01 SEP 2027

Original Issue Date: 2014

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY

INTERNATIONAL LIVING FUTURE INSTITUTE™ living-future.org/declare