



Mohawk Group

Distributed by:
Mohawk Industries
150 South Industrial Blvd.
Calhoun, GA 30701
Phone: 800-554-4637
Fax: 877-244-4054
mohawkgroup.com

**Homogeneous
Resilient Tile**

**Deep
Scrub
Cleaner**

FOR PROFESSIONAL USE
DANGER: CAUSES SERIOUS
SKIN BURNS AND EYE DAMAGE.
See precautions and first aid statement
on side panel. KEEP OUT OF REACH OF
CHILDREN.

**ONE
QUART**

Features & Benefits

Automatically included in every
Homogeneous Resilient Tile order

Biodegradable

Preps and conditions
Homogeneous Resilient Tile

Easy to apply with mop, swing
machine, or auto scrubber

Deep Scrub Cleaner

HOMOGENEOUS RESILIENT TILE TECHNICAL DATA SHEET (TDS)

Mohawk Group Homogeneous Resilient Tile Initial Deep Scrub Cleaner is the first step in the overall Mohawk Group Homogeneous Resilient Tile Flooring Initial Maintenance System. Homogeneous Resilient Tile Initial Deep Scrub Cleaner meets or exceeds green industry standards for floor care products based on its reduced levels of volatile organic compounds and biodegradability. Used in conjunction with the Mohawk Industries Initial Deep Scrub Pad (maroon in color) it deep cleans, preps, and conditions any new Mohawk Industries Homogeneous Resilient Tile tile floor by thoroughly removing deep down manufacturing residue and ground in installation debris. Deep scrub cleaning, using Mohawk Industries Homogeneous Resilient Tile Initial Deep Scrub Cleaner is required before cleaning the surface of the floor.

Specifications

Color..... Yellow to Amber

Fragrance..... Characteristic

pH Range 12.0–12.5

Dilution

Deep Scrub (New Installation): 1:64
(2 oz. per gallon of water)

Light Stripping (2-3 coats of Matte Floor Finish
applied): 1:20 (6 oz. per gallon of water)

Heavy Stripping (more than 3 coats of Matte Floor
Finish applied): 1:10 (13 oz. per gallon of water)

Precautions

KEEP OUT OF REACH OF CHILDREN.

See container and MSDS for further safety
instructions.

Directions for Use

WEAR SAFETY GLASSES AND GLOVES.

- Sweep or dust mop floor to remove debris.
- Do not use oil-based treated dust mops.
- Apply liberal amounts of solution uniformly to floor with a mop.
- Let stripper solution soak for 5 minutes.
- DO NOT ALLOW SOLUTION TO DRY ON FLOOR.
- Scrub floor with an automatic scrubber or stripping machine (350 rpm max).
- Use an automatic scrubber, wet vac or mop and bucket to pick up dirty solution.
- Mop up any tracks left by automatic scrubbers before they dry.
- Rinse thoroughly and detail mop floor with clean water and clean mop.
- Let floor dry completely before applying finish.

NOTE: It is very important to follow the specific directions for cleaning Mohawk Group Homogeneous Resilient Tile. Treating it otherwise can negatively impact visual appearance.

IMPORTANT: Never buff in excess of 350 RPM

FOR DETAILED SITE SPECIFIC INSTRUCTIONS, contact Mohawk Technical Services at 888-387-9881 Option #3 for job specific recommendations