





### Features & Benefits

Automatically included in every Homogeneous Resilient Tile order

Micro-cleans and conditons Homogeneous Resilient Tile

Chemically seals tile

Leaves floors with a natural matte finish

## Matte Floor Finish

# HOMOGENEOUS RESILIENT TILE TECHNICAL DATA SHEET (TDS)

Homogeneous Resilient Tile Matte Floor Finish is the second step in the overall Mohawk Group Homogeneous Resilient Tile Flooring Initial Maintenance System. It is an acrylic finish designed for Mohawk Group Homogeneous Resilient Tile flooring. It provides a protective layer while delivering a natural matte finish. The resulting matte appearance helps reduce the visibility of scuffs and blemishes and supports a clean, even look over time. Apply after the Deep Scrub process to ensure optimal protection and appearance.

## **Specifications**

Color	White
Fragrance	None
pH Range	7.5–8.5
Dilution	RTU
Density	8.59

#### **Precautions**

KEEP OUT OF REACH OF CHILDREN. See container and MSDS for further safety instructions.

#### **Directions for Use**

- 1. Ensure floor is clean and completely dry after the Deep Scrub process.
- Apply Mohawk Homogeneous Resilient Tile Matte Floor Finish in a uniform coat using a microfiber flat mop system with a microfiber finishing pad.
- 3. Apply finish liberally to the mop head for even coverage without over saturating.
- Allow finish to air dry approximately 30–45 minutes before applying the next coat. More time may be needed in high humidity.
- 5. Apply at least two coats for optimal results.

NOTE: Mohawk Group Homogeneous Resilient Tile Matte Floor Finish leaves floors with a natural matte finish.

It is very important to follow the specific directions for cleaning Mohawk Group HT. Treating it otherwise can negatively impact visual appearance.

FOR DETAILED SITE SPECIFIC INSTRUCTIONS, contact Mohawk Technical Services at 888-387-9881 Option #3 for job specific recommendations