



Infuze Seam Sealer

A non-flammable 100% solids, one component, cross linking, modified silane polymer based seam sealer formulated for the seaming of vinyl backed sheet goods.

APPLICATION

1. Prepare vinyl according to Mohawk Group's commercial installation instructions.
2. Apply a bead (approximately 1/8") along the entire edge of the commercial sheet vinyl. Apply seamsealer to only one side of the vinyl to be seamed.
3. Complete the seam by tucking both sections of the sheet vinyl together while the adhesive is still wet.
4. Roll seam with a hand roller to remove excess seam sealer.
5. Always recap seam sealer between applications.
6. Remove any excess seam sealer by wiping with a clean dry cloth, followed by a cloth dampened with mineral spirits.
7. Dried sealer may be removed with approved adhesive remover/stripper
8. Protect the seam area for a minimum of 6 hours to allow seam to fully cure.

PHYSICAL PROPERTIES

Base: Modified Silane Polymer Blend

Appearance: White, smooth, creamy, easy to apply

Shelf Life: One year in unopened container at 70°F (21.10° C)

Coverage: Approximately 140 to 150 linear feet/5 oz. tube

Other Features: Waterproof when cured

VOC compliant, non-flammable, freeze-thaw stable to 10° F (-12.22° C)

Clean Up: Use Mineral Spirits, approved Adhesive Remover/Stripper

CAUTION

DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately.
KEEP OUT OF REACH OF CHILDREN.

WARRANTY INFORMATION: This product is manufactured according to exacting quality control standards and warranted to be free from manufacturing defects. Defective material called to our attention within one year of manufacture will be replaced. No guarantee, expressed or implied is made regarding the performance of this product since the manner and conditions of application are beyond our control. For complete warranty information, call Mohawk Group Technical Services at 800.833.6954. You may also visit us on the web at www.mohawkgroup.com.