



Living Local

Woods 2.5 Woods 4.5



Woods 2.5 | 4.5

Featuring a new selection of some of our most popular wood visuals, Woods 2.5 | 4.5 LVT from the Living Local Collection brings natural warmth and fresh aesthetics to all types of spaces.

The styles provide a palette of 16 plank visuals that range from contemporary to classic grains in an array of colors. Adding versatility, this LVT is offered in two plank sizes as well as 2.5mm and 4.5mm platform thicknesses, enabling seamless transitions to our different types of carpet tile.

With a new level of diversity and adaptability, Woods 2.5 | 4.5 is the perfect solution for almost any project. Made in the USA with M-Force® Ultra technology, these styles deliver outstanding quality, durability, and fresh inspiration for biophilic environments.



Learn more at mohawkgroup.com

Cover:
Woods 2.5 | 4.5, 855 Bly, 822 Unicoi





Woods 2.5 | 4.5, 220 Bridal Veil
Stones 2.5 | 4.5, 225 Chiseled Edge







Colorways

Whether you're looking for a favorite or fresh option, Woods 2.5 | 4.5 brings together a spectrum of aesthetics for your designs. Choose from a range of warm and cool tones with sleek graining, rich variation, or distressed effects.



095 Studio



220 Bridal Veil



812 Tan Tone



822 Unicoi



832 Tellico



838 Cumberland



839 Burney



855 Bly



862 Marion



865 Roan



868 Yosemite



918 Silver



938 Tray



939 Racehorse



958 Two Tone



978 Woody



Ultra Performance and Worry Free Solutions for Any Project

Woods 2.5 | 4.5 is available in two thicknesses, offering a seamless transition to a variety of soft surfaces and helping you meet the needs of different projects. Both products are designed with a 20 mil heavy commercial wear layer and our premium M-Force® Ultra technology, which delivers a complete performance system for LVT.

M-Force® Ultra

Living Local features our M-Force® Ultra technology providing exceptional scratch, stain and dent resistance, and easy maintenance for lasting beauty.



Living Local is manufactured in our innovative closed-loop facility in Georgia, with optimized material sourcing and reduced emissions in the distribution process.



All our flooring products go Beyond Carbon Neutral, meaning they are 100% carbon neutral plus an additional 5% carbon offset for a Net-Positive impact.



2.5MM FLEX

Reducing installation time and costs, no transition strips are needed between the 2.5mm platform and EcoFlex® Matrix backed carpet tile.

- May contribute toward LEED/WELL
- UL certified EPD
- No ortho-phthalates
- FloorScore® certified for low VOCs



4.5MM FLEX

Reducing installation time and costs, no transition strips are needed between the 4.5mm platform and EcoFlex® ONE or EcoFlex® AIR backed carpet tile.

- May contribute toward LEED/WELL
- UL certified EPD
- No ortho-phthalates
- FloorScore® certified for low VOCs



connectD 2.5 | 5.0, 910 Gentle Haze
Creative Culture, 829 Sisal Running Line Rug with Serged Edge

Running Line Rug Program

Unlock your creative freedom with our innovative Running Line Rug Program. Dive in and explore our carefully curated styles, mix and match colors, sizes, and edge treatments to create the perfect rug for your space.



Elemental Edges WALL BASE

Elemental Edges is a portfolio of architectural and cove wall base for your finishing needs. Featuring a range of colors that coordinate with our full product line, Elemental Edges also offers 14 stocked colors in cove wall base.



Specifications

Woods 2.5mm (C2121)
Woods 4.5mm (C2120)

DESIGN

Product Type	Luxury Vinyl Tile - Flexible
Overall Thickness	2.5mm 4.5mm
Wear Layer	20 mil (0.5mm)
Finish	M-Force® Ultra
Colors	16
Size	7" x 48"
2.5mm	9.25" x 59"
4.5mm	Overall
Emboss	Square Edge
Edge Profile	Glue Down
Installation & Adhesive	
Packaging	18 pcs per carton / 42 sq ft per carton 7 pcs per carton / 26.52 sq ft per carton
2.5mm	
4.5mm	
For detailed adhesive and installation information visit mohawkgroup.com	

PERFORMANCE

Construction	Commercial Flexible Luxury Vinyl Tile
Classification	ASTM F1700 - Class III, Type B - Embossed
Squareness	ASTM F2421 - Passes - $\pm 0.10"$ max
Size and Tolerance	ASTM F2421 - Passes - $\pm 0.016"/$ linear foot
Thickness	ASTM F386 - Passes, as specified $\pm .005"$
Flexibility	ASTM F137 - Passes - 1" mandrel
Dimensional Stability	ASTM F2199 - Passes - 0.020"/linear foot max
Static Load Limit	ASTM F970 - Passes, modified at 1000 psi
Residual Indentation	ASTM F1914 - Passes, Avg less than 8%, Max Single Reading 10%
Resistance to Chemicals	ASTM F925 - Passes - No more than a slight change
Resistance to Light	ASTM F1515 - Passes, $\Delta E \leq 8$
Resistance to Heat	ASTM F1514 - Passes, $\Delta E \leq 8$
Critical Radiant Flux	ASTM E648 - Class 1 (>0.45 W/cm2)
Smoke Density	ASTM E662 - Meets, 450 or less

SUSTAINABILITY

Certification	FloorScore® Certified
---------------	-----------------------

SERVICE

Warranties	Limited 20 Year M-Force® Ultra Commercial
For detailed warranty information visit mohawkgroup.com	



RECOVER
RECYCLING PROGRAM

Through Mohawk's ReCover Recycling Program over 160 million pounds of flooring has been diverted from landfills and giving a second life. We accept flooring from any manufacturer and will manage your entire recycling process.





Mohawk Group

Mohawk Group
160 South Industrial Blvd.
Calhoun, GA. 30701
800.554.6637
mohawkgroup.com

MG807 12PG BROCHR LT