



Mohawk M45

Technical Data Sheet (TDS)

Wall Base Adhesive

Mohawk M45 is a premium light-colored and solvent-free acrylic adhesive designed for difficult to bond cove base. Used for installing vinyl (PVC), rubber and specialty cove base on clean, dry interior walls. M45 has the high grab and wet strength to keep corners tight and to hold cove base to the wall until it dries. The fast-setting formula provides a durable impact-resistant bond.

Advantages

Compatible with All Common Manufactured Brands of Cove Base

Non-staining

SCAQMD Rule 1168 - Compliant

Low Odor

Easy Clean Up

Freeze Thaw Protected to 15° F

Exceptional Wet Grab



BEFORE YOU BEGIN

Follow Mohawk Group instructions regarding trowel size, coverage and application methods. Make certain the surface is porous by cutting away or perforating non-absorbent wall coverings. Do not apply to vinyl wallpaper. Mohawk cannot be responsible for shrinkage caused by unstable cove base.

INSTALLATION

- Spread the adhesive using a 1/8" x 1/8" V-Notch trowel, or using a tube applicator tip.
- The adhesive may be spread on the wall surface or on the back of the wall base.
- Immediately place the wall base into position while the adhesive is freshly applied.
- Roll the entire strip of base with a small roller in the direction of the previously placed strip.
- Wipe smudges and clean spills quickly before the adhesive dries. Use a clean cloth dampened with water.
- Clean tools with water while the adhesive is still wet.
- Dried adhesive may require the use of a solvent (odorless mineral spirits).

USE OVER

Plaster, brick, wood, concrete, gypsum drywall, plywood.

RECOMMENDED COVERAGE AND TROWEL

Standard 4" Cove 3 hole applicator
Coverage- 55-60 linear feet per cartridge
1/8" x 1/8" x 1/8" V-Notch (220-240 LF/gal)

ADHESIVE WORKING TIME

20-30 minutes

SHELF LIFE

2 years from manufacturing date in an unopened container

This product is not photochemically reactive as defined by California Rules 102 and 443. VOC content is below that established by California SCAQMD Rule 1168.