

Healthy Environments

Medella Fleck N

Medella Hues

Healthy Environments

Ш

Medella Fleck and Medella Hues are designed to enhance demanding environments. The two styles deliver longlived performance in healthcare, education, hospitality, workplace, and retail spaces.

With durable M-Force[™] Xtreme technology, Medella Fleck and Medella Hues are NFSI High Traction Certified and achieve an R10 slip resistance rating, while being easy to clean and meeting an ISO Class 3 Certification for cleanrooms.

With a 20-year commercial warranty and 20-year underbed warranty*, Medella Fleck and Medella Hues combine evidence-based design, technology, and innovation to extend the quality and longevity of your spaces.

*When installed with approved adhesives. For detailed information visit, mohawkgroup.com.

Medella Applications

V	Patient & Exam Rooms	V	Activity Rooms
V	ICU/OR	V	Physical Therapy
V	Clean Rooms	V	Food Services
V	Life Science & Laboratory	V	Science Classrooms
~	Corridors	V	Cafeterias



Learn more at mohawkgroup.com

Cover: Medella Fleck 84197 Silver Gray, Medella Hues H5431 Serenity Buzzing Trails 739



Medella Hues H5301 Gray Light, H5307 Dust Gray Light

Medella Fleck & Medella Hues

Medella Fleck and Medella Hues homogeneous resilient sheet with M-Force[™] Xtreme provide spaces with a holistic flooring solution. In addition to the advantages described below, these flooring styles install with welded seams to create a wall-to-wall impermeable floor, delivering superior infection control as well as moisture resistance.

M-Force[®] Xtreme Performance For Life

Medella Fleck and Medella Hues feature M-Force[™] Xtreme technology for exceptional resistance to abrasions, scratches, punctures, and stains, providing long-term durability with a limited 20year commercial warranty.



SLIP RESISTANCE CERTIFIED

Medella Fleck and Medella Hues are NFSI Certified High Traction in wet conditions and achieve an R10 slip resistance rating on the DIN 51130 Anti-Slip Properties Ramp Test, ensuring reliable traction.



BEYOND CARBON NEUTRAL

Healthy Environments is Beyond Carbon Neutral, for a Net-Positive impact.



BETTER TOGETHER As part of our Specify for the Cure program, Mohawk Group will donate on your behalf to Susan G. Komen for qualifying specifications of this collection.



SUSTAINABLE

All Healthy Environments resilient sheet products are FloorScore certified and have an ASTM certified EPD for better indoor air quality. These products can be recycled through the Mohawk Group Recover program.



Elemental Edges WALL BASE

Elemental Edges is a portfolio of architectural and cove wall base for your finishing needs. Featuring a range of colors that coordinate with our full product line, the collection also offers 14 stocked colors in cove wall base.





Medella Hues COLORWAYS

Medella Hues provides a wide variety of neutrals and brights, expanding the design possibilities of your floor.



H5362 Sage

H5403 Brown Umbra

H5406 Ocean Blue



H5333 Stream Blue

H5334 Scarlet

H5335 Feldspar



H5336 Night Sky

Medella Hues Weld Rods COLORWAYS

Coordinating weld rods are available for all Medella Hues colorways, in solid and patterned options.

Solid

SKU: MHSWR 164 Linear Feet		
H5300 Icy White		
H5301 Ash Light		
H5302 Ash		
H5303 Asphalt		
H5304 Steel Gray Light		
H5305 Steel Gray		
H5306 Steel Gray Dark		
H5307 Pebble Gray Light		
H5308 Pebble Gray Mid		
H5310 Boulder Brown		
H5311 Cream White		
H5312 Decaf		
H5313 Gray Tan		
H5316 Beige		
H5319 Toffee Light		
H5320 Toffee Mid		
H5328 Steel Blue Light		
H5329 Steel Blue Mid		
H5350 Mid Cobalt		
H5351 Dark Cobalt		
H5358 Spearmint		
H5362 Calm Green		

Patterned

SKU: MHPWR | 82 Linear Feet

H5300 Cool White	
H5301 Gray Light	
H5302 Deep Gray	
H5303 Almost Black	
H5304 Natural Gray Light	
H5305 Natural Gray	
H5306 Natural Gray Dark	
H5307 Dust Gray Light	
H5308 Dust Gray Mid	
H5310 Rock	
H5311 Natural White	
H5312 Natural	
H5313 Natural Tone	
H5316 Light Chocolate	
H5319 Sand Light	
H5320 Sand Mid	
H5328 Steel Light	
H5329 Steel Mid	
H5350 Indigo Mid	
H5351 Indigo	
H5358 Soft Green Light	
H5362 Sage	

Solid

SKU: MHSWR | 164 Linear Feet

SKU: MHSWR 164 Linear Feet				
H5403 Dark Roast				
H5406 Royal Blue				
H5408 Limeaid				
H5420 Pitch Black				
H5421 Henna				
H5422 Mocha				
H5423 Sunshine				
H5424 Orange Peel				
H5425 Blood Orange				
H5426 Pomegranate				
H5427 Grape				
H5428 Plum				
H5431 Beach Blue				
H5432 Navy Yard				
H5433 Army Blue				
H5434 Ocean Wave				
H5435 Astroturf				
H5436 Dandelion				
H5438 Dark Lilac				
H5532 Steel Blue				
H5331 White				
H5332 Green				
H5333 Blue				
H5334 Red				
H5335 Russet				
H5336 Night Blue				

Patterned SKU: MHPWR | 82 Linear Feet

H5403 Brown Umbra	
H5406 Ocean Blue	各权益相關的
H5408 Lime	
H5420 Little Black Book	
H5421 Hazel	
H5422 Walnut	
H5423 Golden Sun	4.1011年1月1日
H5424 Zaffron	
H5425 Tangerine	
H5426 Fuchsia	
H5427 Perfectly Plum	
H5428 Hydrangea	
H5431 Serenity	
H5432 Regatta	
H5433 Lagoon	
H5434 Mazarine	
H5435 Pine	
H5436 Maize	
H5438 Light Aubergine	
H5532 Grayed	
H5331 Birch	
H5332 Salt Spray	
H5333 Stream Blue	
H5334 Scarlet	國新統制

H5335 Feldspar

H5336 Night Sky

Medella Fleck COLORWAYS

Medella Fleck features soft colors and a rich visual texture, infusing the indoors with nature's beauty.



84163 Almond



84197 Silver Gray



84410 Color Fleck



84620 Chateau Gray



84880 Sky



84982 Fog



84986 Shore Sand



84989 Starry Night






84970 Sandstone



84983 Stone Dust




84987 Stone Wall



84980 Snow



84985 Morning Haze



84988 Alpine Lake



84850 Pearl

Medella Fleck Weld Rods COLORWAYS

Coordinating weld rods are available for all Medella Fleck colorways, in solid and patterned options.

Solid

SKU: MFSWR 164 Linear Feet		
84163 Almond Milk		
84197 Light Sterling		
84410 Pollock		
84620 Charcoal		
84760 Dawn Gray		
84850 Rosy Pearl		
84880 Snowflake		
84970 Sandstorm		
84980 Icy White		
84982 Fog Gray		
84983 Dust		
84985 Morning Gray		
84986 Sand Tan		
84987 Wall Gray		
84988 Alpine		
84989 Night Black		

Patterned

SKU: MFPWR | 82 Linear Feet

84163 Almond	
84197 Silver Gray	
84410 Color Fleck	
84620 Chateau Gray	
84760 Shell	
84850 Pearl	
84880 Sky	
84970 Sandstone	
84980 Snow	
84982 Fog	
84983 Stone Dust	
84985 Morning Haze	
84986 Shore Sand	and the second
84987 Stone Wall	
84988 Alpine Lake	
84989 Starry Night	

M-Force[™] Xtreme FOR SHEET

Discover a hard surface flooring solution that delivers superior durability and stain resistance, ensuring ease of care for the life of the floor. Mohawk Group's Resilient Sheet Flooring with M-Force™ Xtreme provides elegant design and performance solutions for healthcare spaces.

PERFORMANCE

- Provides exceptional resistance to abrasions, scratches, and punctures for lasting beauty.
- Homogeneous resilient construction provides enhanced protection from cuts or gouges.
- Proven to meet stringent particulate and cleanliness requirements for controlled environments: Certified for ISO 14644 cleanroom standards.


CLEANABILITY

- Remains 100% stain-free against common staining agents, as tested per ANSI/NALFA LF-01 Section 3.4 - Cleanability and Stain Resistance.
- Provides the highest ease of cleaning and resistance to soiling, as tested per the BS EN 14565 Hexapod Soiling Test.

SAFETY

- NFSI Certified High Traction in wet conditions.
- Achieves an R10 slip resistance rating and ensures reliable traction, as tested per the DIN 51130 Anti-Slip Properties Ramp Test.

Homogeneous Resilient Sheet



WATER RESISTANCE

 With welded seams and a water-repellent finish, Healthy Environments resilient styles create impermeable flooring systems.

ISO Class 3 Cleanroom

With M-Force[™] Xtreme, Medella helps create safer, healthier spaces that meet the highest cleanliness requirements.

- Meets ISO 14644-1 cleanroom standards at ISO Class 3.
- Certification ensures that Medella flooring supports strict standards for air cleanliness.
- Reduces the generation and buildup of airborne particulates in the environment.
- Ideal for hospitals, labs, and other areas where maintaining a clean and controlled atmosphere is critical.

Backed by 20-Year Warranties

- Limited 20-Year Commercial Warranty
- Limited 20-Year Commercial Under Bed Warranty*

*When installed with approved adhesives. For detailed adhesive and installation information, visit mohawkgroup.com.

Slip Resistance Certified



Tested to Ensure Reliable Traction

Medella flooring achieves an R10 slip resistance rating in the DIN 51130 Anti-Slip Properties Ramp Test, ensuring reliable traction.

NFSI Certified High Traction in Wet Conditions

Medella is the only resilient sheet flooring on the market with high traction certification from the National Floor Safety Institute (NFSI).

Advantages of NFSI High Traction Testing

- NFSI measures slip resistance on wet flooring, where slip-and-fall injuries typically occur.
- NFSI measures slip resistance in static and dynamic situations, akin to standing and walking.
- NFSI tests a flooring sample and a field installation.
- ASTM D2407 only tests on dry flooring.
- ASTM D2407 only tests using the static method, offering no insight on slip resistance when walking.
- ASTM D2407 only tests a flooring sample in a lab.

TEST METHOD	NFSI B101.1* & B101.3+	ASTM D2047
Dry floor		V
Wet floor	\checkmark	
Static* (stationary)	\checkmark	V
Dynamic+ (in motion)	\checkmark	
Sample tested in lab	\checkmark	V
Field installation for at least 30 days	\checkmark	



Resilient Sheet Solutions

Weld Rods

Mohawk Group's solid or patterned heat weld rods are recommended for Medella Fleck and Medella Hues. The weld rods are offered in solid coordinating colorways and used for seaming, wayfinding or accenting.

HEAT WELD / COLD WELD


Optional heat welding or cold welding techniques can be used to create seamless, sanitary flooring that's easy to maintain. Order weld rods using the SKUs shown below for the style number, followed by the coordinating Medella Fleck or Medella Hues color number. Place order using "INFZC" for the Infuze Seam Sealer.

Resilient Sheet Solid Weld Rods (164 LF per roll)

- Medella Fleck Solid MFSWR
- Medella Hues Solid MHSWR



Scan to see our suggested weld rod color coordinates for Medella styles.



Resilient Sheet Patterned Weld Rods (82 LF per roll)

- Medella Fleck Patterned MFPWR
- Medella Hues Patterned MHPWR

Installation and Applications

Medella flooring includes solutions for a more efficient and effective installation, as well as a guide to the variety of project applications and segments where these products excel.

IN-HOUSE CUT PROGRAM

- Medella Fleck and Medella Hues can be cut to the roll size you need with our in-house cut program
- No order minimum required

PROJECT SOLUTIONS

- MS160 spray adhesive can be used for projects where immediate occupancy is needed
- Medella Fleck and Medella Hues can be flash coved for enhanced sanitary protection.



Scan to see our recommended application guide.



Specifications

Medella Fleck (C2061) Medella Hues (C2062)

DESIGN

Width **Overall Thickness** Finish Colors Available Medella Fleck Medella Hues Seaming Method Packaging

PERFORMANCE

Construction

Classification Flexibility Thickness Static Load Limit **Residual Indentation** Resistance to Chemicals Resistance to Light Resistance to Heat Critical Radiant Flux Smoke Density Slip Resistance

Cleanroom

SUSTAINABILITY

Certification Indoor Air Quality Carbon

SERVICE

Warranties

Limited 20-Year Commercial Limited 20-Year Under Bed Warranty*

*When installed with approved adhesives. Visit mohawkgroup.com for more information

Mohawk Group warrants its adhesives for the life of the original installation only when a Mohawk Group style (product) is installed. Mohawk's floor preparation procedures must be followed to ensure that the substrate has been prepared properly. The use of Mohawk Group approved adhesives is required to ensure optimum results and are the only adhesives warranted by Mohawk Group. Please contact your local Sales Representative for installation guidelines.

6'7" (2.0 m)

16

48

0.080" (2.0 mm)

M-Force[™] Xtreme

Roll Length - Up to 98.4' (30 m)

visit mohawkaroup.com

Mohawk Group is providing this architect folder for the purpose of promoting our commercial business. This folder and its samples shall remain the property of Mohawk Group. Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations or other factors. The performance of this product is not affected by such variations. For current and complete specifications please visit mohawkgroup.com



REC RECYCLING PROGRAM

Give your old flooring a second life with our award-winning ReCover Recycling Program. We will take away flooring made by any manufacturer, recycle it for you, and provide a certificate showing your positive impact on the planet.



Non-ortho Phthalate Construction ASTM F1303 - Meets or Exceeds ASTM F137 - Passes ASTM F386 - Passes, as specified ± .005" ASTM F970 - Passes, ≤ 0.1 mm, modified to 2,000 psi ASTM F1914 - Passes, Average less than 8% ASTM F925 - Passes ASTM F1515 - Passes, $\Delta E \le 8$ ASTM F1514 - Passes, $\Delta E \le 8$ ASTM E648 - Meets, Class 1 ASTM E662 - Meets, 450 or less NFSI B101.1 - NFSI Certified High Traction NFSI B101.3 - NFSI Certified High Traction DIN 51130 Anti-Slip Properties Ramp Test - R10 Rating

Commercial Grade Homogeneous Resilient Sheet

Mohawk Solid or Patterned Heat Weld Rod or Cold Weld

For detailed adhesive and installation information

ISO 14644-1- ISO Class 3 Certified

Environmental Product Declaration FloorScore® Certified Net-Positive Carbon (Neutral +5%)



Mohawk Group 160 South Industrial Blv Calhoun, GA. 30701 800.554.6637 mohawkgroup.com

Mohawk Group

MG766 16PAG BROCHR LT