



PrimeCoat Concrete Floor Primer

DESCRIPTION

PrimeCoat is a topically applied modified acrylic floor primer used to treat dry, dusty or porous substrates for a better bonding surface and to help ensure proper adhesive bond. **PrimeCoat** may also be used to prime gypcrete surfaces and to de-tack adhesive residues. Apply one coat of PrimeCoat with a 3/8" nap roller as an even coat over the entire surface of the floor at a rate of 35–40 square yards per gallon. Allow the floor to dry completely after application.

FEATURES

- Solvent-Free
- Very Low Odor
- Dries Quickly to a Clear Film
- Tinted Green for Easy Identification

PrimeCoat is recommended to prime porous or dry sub-floors before installations to provide a smooth tack-free surface that will improve adhesive application. Before applying, scrape down ridges and remove as much of old adhesive as possible. Patching or leveling of sub-floor must follow all manufacturers' application and curing instructions prior to applying **PrimeCoat**.

Do not use **PrimeCoat** to encapsulate cutback adhesive residues or as a sealer. Installation jobsites must be air conditioned with HVAC in operation. The floor and room temperature, as well as the **PrimeCoat** should be between 65° and 95° F and the humidity should be between 10% and 65% for 48 hours prior to, during and after the installation.

To clean up while wet, use soapy water; when dry, use of a solvent may be required. Containers must be kept tightly closed. Protect from freezing.

APPLICATION AND COVERAGE

3/8" Nap Roller – 35–40 square yards per gallon

This product is not photochemically reactive as defined by California Rules 102 and 443. VOC emission levels are well below those established by the California SCAQMD Rule 1168.

