



## SECOND WAVE SY023

### Specification

<b>Product Type:</b>	Broadloom
<b>Construction:</b>	Tufted
<b>Surface Appearance:</b>	Textured Patterned Cut & Loop
<b>Gauge:</b>	1/12 (47.00 rows per 10 cm)
<b>Tufted Face Weight:</b>	36 oz/yd <sup>2</sup> (1,221 g/m <sup>2</sup> )
<b>Pile Thickness:</b>	.200" (5.08 mm)
<b>Stitches Per Inch:</b>	12.0 (47.24 per 10 cm)
<b>Dye Method:</b>	Precision Dye Injection
<b>Fiber Type:</b>	Colorstrand® Nylon
<b>Stain Release Technology:</b>	Sentry Plus Stain Protection
<b>Soil Release Technology:</b>	Sentry Soil Protection
<b>Density:</b>	6,480
<b>Weight Density:</b>	129,600
<b>Backing Type:</b>	Weldlok®
<b>Pattern Repeat:</b>	18" (W) x 19.5" (L)
<b>Width:</b>	10', 12' and 15' widths available
<b>Flammability:</b>	ASTM E 648 Class 1 (Glue Down)
<b>Smoke Density:</b>	ASTM E 662 Less than 450
<b>Static Propensity:</b>	AATCC-134 Under 3.5 KV
<b>IAQ Green Label Plus:</b>	6678
<b>Warranties:</b>	10 Year Limited Wear Warranty Lifetime Static

All specifications are subject to normal manufacturing tolerances

7/19