



SECOND WAVE TILE SY022

Specification

Product Type:	Carpet Tile
Construction:	Tufted
Surface Appearance:	Textured Patterned Cut & Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Tufted Face Weight:	36 oz/yd ² (1,221 g/m ²)
Pile Thickness:	.205" (5.21 mm)
Stitches Per Inch:	12.0 (47.24 per 10 cm)
Dye Method:	Precision Dye Injection
Fiber Type:	Colorstrand® Nylon
Stain Release Technology:	EcoSentry Plus Stain Protection
Soil Release Technology:	EcoSentry Soil Protection
Density:	6,322
Weight Density:	227,592
Backing Type:	EcoFlex® NXT Air
Installation Method Planks:	Monolithic / Brick Ashlar / Monolithic Stepping
Installation Method Squares:	Monolithic / Brick Ashlar / Vertical Ashlar
Size:	12" x 36" planks or 24" x 24" squares
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450
Static Propensity:	AATCC-134 Under 3.5 KV
IAQ Green Label Plus:	1256
Warranties:	10 Year Limited Carpet Tile Warranty Lifetime Static

All specifications are subject to normal manufacturing tolerances

7/19