



## SHAKA II TILE SY030

### Specification

<b>Product Type:</b>	Carpet Tile
<b>Construction:</b>	Tufted
<b>Surface Appearance:</b>	Textured Patterned Cut & Loop
<b>Gauge:</b>	1/12 (47.00 rows per 10 cm)
<b>Tufted Face Weight:</b>	26 oz/yd <sup>2</sup> (882 g/m <sup>2</sup> )
<b>Pile Thickness:</b>	.120" (3.05 mm)
<b>Total Thickness:</b>	.278" (7.06 mm)
<b>Stitches Per Inch:</b>	10.5 (41.37 per 10 cm)
<b>Dye Method:</b>	Precision Dye Injection
<b>Fiber Type:</b>	Colorstrand® Nylon
<b>Stain Release Technology:</b>	EcoSentry Plus Stain Protection
<b>Soil Release Technology:</b>	EcoSentry Soil Protection
<b>Density:</b>	7,800
<b>Weight Density:</b>	202,800
<b>Backing Type:</b>	EcoFlex® AIR
<b>Installation Method:</b>	Monolithic / Brick Ashlar / Vertical Ashlar
<b>Size:</b>	12" x 36" planks or 24" x 24" squares
<b>Flammability:</b>	ASTM E 648 Class 1 (Glue Down)
<b>Smoke Density:</b>	ASTM E 662 Less than 450
<b>Static Propensity:</b>	AATCC-134 Under 3.5 KV
<b>CRI Appearance Retention Rating:</b>	Severe
<b>IAQ Green Label Plus:</b>	1256
<b>Warranties:</b>	Lifetime Limited Carpet Tile Warranty Lifetime Limited Colorfastness to Light 10 Year Limited Colorfastness to Atmospheric Contaminants 10 Year Stain Warranty Lifetime Static

All specifications are subject to normal manufacturing tolerances.

2/24