



Commercial Nylon Broadloom Carpet on Weldlok ComfortGuard Mohawk Group

Final Assembly: Dalton, Georgia, USA

Life Expectancy: 15 Year(s)

Embodied Carbon: 13.2 kg CO2 eq 

Declared Unit: 1 m2

End of Life Options: Salvageable/Reusable in its Entirety, Take Back Program (ReCover)

Ingredients:

Calcium Carbonate; Nylon 6; Polyurethane foams; Styrene-butadiene copolymers; Polyethylene Terephthalate; 1-Propene, homopolymer, isotactic; Titanium dioxide; 1H-Indene-1,3(2H)-dione, 2-(3-hydroxy-2-quinoliny)-; 2-Naphthalenesulfonic acid, 6-amino-4-hydroxy-5-[[2-(trifluoromethyl)phenyl]azo]-, monosodium salt; 2-Naphthalenesulfonic acid, 6-amino-5-[[4-chloro-2-(trifluoromethyl)phenyl]azo]-4-hydroxy-, monosodium salt; 9,10-Anthracenedione, 1,5-diaminochloro-4,8-dihydroxy-; 9,10-Anthracenedione, 1,8-dihydroxy-4-nitro-5-(phenylamino)-; Benzenesulfonic acid, 4-[[4-[2-(4-hydroxy-2-methylphenyl)diazenyl]phenyl]amino]-3-nitro-, sodium salt (1:1); C.I. Acid Blue 324; C.I. acid red 426; C.I. Disperse Yellow 64 (primary CASRN is 10319-14-9); Remazol Gold Yellow RNL; Quartz; Water; Sulfuric acid, mono-C10-16-alkyl esters, ammonium salts; 1-Dodecanol; 2-Propenoic acid, 2-methyl-, polymer with ethyl 2-propenoate, sodium salt

Living Building Challenge Criteria: Compliant

I-13 Red List:

- LBC Red List Free % Disclosed: 100% at 100ppm
- LBC Red List Approved VOC Content: Not Applicable
- Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

MHK-0044
EXP. 01 JUL 2027
Original Issue Date: 2026