

PRODUCT SPECIFICATIONS

Construction	Glazed Ceramic
Use	Residential
Finish	Matte
Application(s)	Floor/Wall/Backsplash/Countertop
Edge	Pressed
Installation*	3/16"
Shade Variation	V2
D.C.O.F. (Slip Resistance)	≥ 0.42
P.E.I. (Wear Resistance)	3
Scratch Hardness	5
Frost Resistance	Not Resistant




Sizes are Nominal. Dye lot & Texture variations are inherent characteristics of this product.

AVAILABLE SIZES



12" x 24"



12" x 12"



18" x 18"



3" x 3"



3" x 12" BN

*Recommended Grout Joint: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)



COLOR NAME	COLOR NUMBER	MASTER SIZE CODE	NORMAL SIZING	BACKING	SF/CTN	PCS/CTN	LBS/CTN	UOM/PLT	UOM	PART#
Volakas White	BB35	1212	12x12	FT	20.00	20	60.60	1020.00	SF	P17532
Volakas White	BB35	1224	12X24	FT	13.78	7	50.71	826.80	SF	P17807
Volakas White	BB35	1818B	18x18	FT	19.60	9	59.52	862.40	SF	P17773B
Volakas White	BB35	S43C9	3x12	BN	-	36	27.50	3600.00	PC	P17531
Volakas White	BB35	33MS	3x3	SH	16.00	16	40.96	1152.00	SH	P17530

FOR MORE INFORMATION, VISIT [MOHAWKBUILD.COM](https://www.mohawkbuild.com)