

PRODUCT SPECIFICATIONS

Construction	Glazed Porcelain
Use	Residential
Finish	Matte
Application(s)	Floor/Wall/Backsplash/Countertop
Edge	Pressed
Installation*	3/16"
Shade Variation	V4
D.C.O.F. (Slip Resistance)	≥ 0.42
P.E.I. (Wear Resistance)	4
Scratch Hardness	8
Frost Resistance	Resistant



Sizes are Nominal. Dye lot & Texture variations are inherent characteristics of this product.

AVAILABLE SIZES



6" x 36"

*Recommended Grout Joint: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)



PRODUCT SPECIFICATIONS

Construction	Glazed Porcelain
Use	Residential
Finish	Matte
Application(s)	Floor/Wall/Backsplash/Countertop
Edge	Pressed
Installation*	3/16"
Shade Variation	V4
D.C.O.F. (Slip Resistance)	≥ 0.42
P.E.I. (Wear Resistance)	4
Scratch Hardness	8
Frost Resistance	Resistant



Sizes are Nominal. Dye lot & Texture variations are inherent characteristics of this product.

AVAILABLE SIZES



6" x 36"

*Recommended Grout Joint: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)



PRODUCT SPECIFICATIONS

Construction	Glazed Porcelain
Use	Residential
Finish	Matte
Application(s)	Floor/Wall/Backsplash/Countertop
Edge	Pressed
Installation*	3/16"
Shade Variation	V4
D.C.O.F. (Slip Resistance)	≥ 0.42
P.E.I. (Wear Resistance)	4
Scratch Hardness	8
Frost Resistance	Resistant



Sizes are Nominal. Dye lot & Texture variations are inherent characteristics of this product.

AVAILABLE SIZES



6" x 36"

*Recommended Grout Joint: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)



PRODUCT SPECIFICATIONS

Construction	Glazed Porcelain
Use	Residential
Finish	Matte
Application(s)	Floor/Wall/Backsplash/Countertop
Edge	Pressed
Installation*	3/16"
Shade Variation	V4
D.C.O.F. (Slip Resistance)	≥ 0.42
P.E.I. (Wear Resistance)	4
Scratch Hardness	8
Frost Resistance	Resistant



Sizes are Nominal. Dye lot & Texture variations are inherent characteristics of this product.

AVAILABLE SIZES



6" x 36"

*Recommended Grout Joint: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)



PRODUCT SPECIFICATIONS

Construction	Glazed Porcelain
Use	Residential
Finish	Matte
Application(s)	Floor/Wall/Backsplash/Countertop
Edge	Pressed
Installation*	3/16"
Shade Variation	V4
D.C.O.F. (Slip Resistance)	≥ 0.42
P.E.I. (Wear Resistance)	4
Scratch Hardness	8
Frost Resistance	Resistant



Sizes are Nominal. Dye lot & Texture variations are inherent characteristics of this product.

AVAILABLE SIZES



6" x 36"

*Recommended Grout Joint: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)



COLOR NAME	COLOR NUMBER	MASTER SIZE CODE	NORMAL SIZING	BACKING	SF/CTN	PCS/CTN	LBS/CTN	UOM/PLT	UOM	PART#
Glacier White	MP40	636	6 x 36	FT	13.05	9	54.03	626.40	SF	P17848
Desert Mist	MP41	636	6 x 36	FT	13.05	9	54.03	626.40	SF	P17849
Aspen Bliss	MP42	636	6 x 36	FT	13.05	9	54.03	626.40	SF	P17850
Enchanted Forest	MP43	636	6 x 36	FT	13.05	9	54.03	626.40	SF	P17851
Coffee Bean	MP44	636	6 x 36	FT	13.05	9	54.03	626.40	SF	P17852

FOR MORE INFORMATION, VISIT [MOHAWKBUILD.COM](https://www.mohawkbuild.com)