

Hard Surface Adhesive Matrix

	Product	Product Description	Moisture	SKU	Size/Pkg	Spread Rate/ Approximate Coverage
ERT Adhesives	M99	High strength, high tack adhesive for installing ERT and LVT planks, and rubber stair treads	99% RH	M99	1 Gal 4 Gal	1/16" x 1/32" x 1/32" U-notch trowel 220-260 SF/Gal
	M99	High strength, high tack adhesive for installing ERT and LVT planks, and rubber stair treads	99% RH	M99	1 Gal 4 Gal	1/16" x 1/32" x 1/32" U-notch trowel 220-260 SF/Gal
	M95	Premium high-strength adhesive for loose lay and glue down LVT	95% RH	M95	1 Gal 4 Gal	1/16"x1/32"x1/32" U-notch trowel 220-260 SF/Gal
	MS160	Spray adhesive with high grab and sheer strength for loose lay and glue down LVT. Allows immediate occupancy	95% RH	MS160	Spray can (6 cans/ case)	140-160 SF/spray can Depends on substrate and flooring type being installed
LVT Adhesives	M700	High-tack, high sheer strength adhesive for glue down LVT	90% RH	VA67	1 Gal 4 Gal	1/16"x1/32"x1/32" U-notch trowel 200-260 SF/Gal
	M1000	High bond strength adhesive for engineered hardwood over concrete substrates only	95% RH	M1000	4 Gal	3/8"x3/16"x3/8"x1/16" Clip-on Trowel Blade attached to top of pail (approximately 35 SF/Gal)
	M92X	Modified Moisture-Cured Urethane Adhesive for Mohawk Engineered Flooring	90% RH	M92X	4 Gal	3/16" x 1/4" x 5/16" V-Notch Trowel 200-240 SF/Gal
Hardwood Adhesives	GLU1	High strength, low VOC, floor glue to bond tongue and groove hardwood	n/a	GLU1	16 oz bottle	124-200 LF/bottle
	M99	High strength, high tack adhesive for installing LVT and planks, and rubber stair treads	99% RH	M99	1 Gal 4 Gal	1/16" x 1/32" x 1/32" U-notch trowel 220-260 SF/Gal
Resilient Sheet Adhesives	M95	Premium high-strength adhesive for loose lay and glue down LVT	95% RH	M95	1 Gal 4 Gal	1/16"x1/32"x1/32" U-notch trowel 220-260 SF/Gal
	AD-777	Acrylic adhesive for rubber tile and sheet for light to heavy foot traffic	85% RH	AWP77	1 Gal 4 Gal	1/32"x1/16"x1/32" U-notch trowel 200-250 SF/Gal
Rubber Adhesives	AD-535	Solvent-Free Two-part Epoxy adhesive for rubber tile and sheet for heavy foot traffic, rolling loads and radiant heated subfloors	85% RH	SFE35	1 Gal	1/32"x1/16"x1/32" U-notch trowel 160-200 SF/Gal
	AD-888	Epoxy Stair Nosing Caulk required for rubber stair treads over concrete, wood or metal.	n/a	AD888	13.5 oz 2 part cartridge system	Up to 30 LF/ 3/8" bead
	Loctite	Chemical weld system for rubber tile and sheet	n/a	LOCHC	1.7 oz cartridge	up to 40 LF/Cartridge
	Product	Product Description	For Use With	SKU	Size/Pkg	Spread Rate/ Approximate Coverage
LVT Underlays	AccuSound	Provides sound reduction and moisture protection under loose lay or glue down LVT	Loose Lay/ Glue Down LVT	VU01	Roll	5 ft W x 40 ft L 200 SF/Roll
	ActiveSound	Provides acoustic improvement and subfloor correction for Clic flooring	Clic LVT	VU02	Carton	3.87 ft W x 27.85 ft L 100 SF/Ctn
Hardwood Underlay	SilentGuard	Floating acoustic underlayment for engineered hardwood installations. Had attached moisture barrier.	Engineered Hardwood	LU7AB	Roll	40" W x 30' L x 0.08" H Roll 100 SF/Roll
Laminate Underlay	SilentGuard	Floating acoustic underlayment for commercial laminate installations. Had attached moisture barrier.	Laminate	LU7AB	Roll	40" W x 30' L x 0.08" H Roll 100 SF/Roll

Hard Surface Adhesive Matrix

		ADHESIVE						UNDERLAYMENT		
		M99	M95	MS160	M700	M1000	M92X	AccuSound	ActiveSound	SilentGuard
Luxury Vinyl Tile	Loose Lay	X	X	X				X		
	Glue Down	X	X	X	X			X		
	Floating / Click								X	
Enhanced Resilient Tile		X								
Resilient Sheet		X	X							
Laminate										X
Hardwood	Engineered					X	X			X