










Grass Valley Collection

Redefining the norm of mixing different materials and styles, Grass Valley offers 10 types of wood mixed with 3 stones. Created with deconstructivism in mind, this collection offers freedom of form and endless opportunities for unique artistic expression.

Features

- 2.5 mm overall thickness
- 8" x 48" wood planks and 12" x 24" stone tiles
- 20 mil wear layer
- Enhanced Urethane Finish

- FloorScore® Certified
- 10 Year Limited Commercial Warranty
- 25 Year Limited Residential Warranty
- Made in USA









872 Toasted Oak



9817 Flint



9411 Gray Mahogany



938 Good Gray



1714 Natural Mahogany



1357 Natural Cherry



32232 Natural Oak



9140 Silver Oak



9211 White Pine



9112 Gray Matter



941 Warm Gray



358 Stippled Gray



colorSTRAND® SD NYLON

PERFORMANCE & DESIGN

- Wide variety of colors for excellent design flexibility
- Unsurpassed colorfastness to light and to atmospheric contaminants
- Excellent durability and longevity of color
- Resistant to harsh cleaning agents
- Mohawk Protection Plus Soil & Stain Resistant Technology

SUSTAINABILITY

• CRI Green Label Plus® Certified

WARRANTY

- Lifetime Limited Wear Warranty
- Lifetime Static Warranty
- Lifetime Limited Colorfastness To Light Warranty
- 10 Year Limited Colorfastness To Atmospheric Contaminants Warranty
- 10 Year Limited Stain Resistance Warranty

UltraSet® Matrix


Aladdin Commercial continues its dedication to sustainable solutions with UltraSet® Matrix, the next generation in carpet tile backing. Using advanced materials and patented engineering, UltraSet® Matrix lowers environmental impact without sacrificing performance. UltraSet® Matrix simplifies floor preparation and installation, greatly reduces sub-floor moisture concerns, and is easier to ship and handle.

PERFORMANCE

- Provides permanent dimensional stability
- Tiles are impervious to moisture damage from spills and water extraction cleaning
- Up to Lifetime Limited Carpet Tile Warranty for: Wear, Static Protection, Edge Raveling/Zippering, Delamination, Dimensional Stability*
- Seamless transitions between carpet and hard surface flooring with 2.5 mm LVT resilient products

INSTALLATION

- Greatly reduces sub-floor moisture concerns and saves money on mitigation
- Worry free installation with no visible moisture Polyolefin backing contains no plasticizers present using our Flexlok Tab System
- Superior construction offers reliability for the life of your installation



SUSTAINABILITY

- UltraSet® Matrix is manufactured using less energy than other carpet tile products
- Contains a minimum of 40% preconsumer recycled content based on total product weight**
- CRI Green Label Plus certified
- Declare Red List Free
- Recyclable
- Able to ship more per box resulting in a lower environmental impact from transportation

^{*}Lifetime or 10 Year Limited Warranty varies by fiber type, please see specifications for details

^{**}Recycled content claim third party verified by UL (Underwriters Laboratory)

Specifications

CARPET TILE	Brand	Go Forward Tile / 1T45 Tufted Pattern Loop 1/12" (47.00 rows per 10 cm) 5,929 100% Solution Dyed Colorstrand® SD Nylon Mohawk Protection Plus Stain Mohawk Protection Plus Soil Non Woven Synthetic UltraSet® Matrix Green Label Plus Certified # 1171 Gold 24" x 24" (.6096 m x .6096 m) 8 sqyd/ctn Ouarter Turn / Brick Ashlar / Vertical Ashlar / Multi Directional / Monolithic ASTM E 648 Class 1 (Glue Down) ASTM E 662 Less than 450	CARPET TILE

Brand	Aladdin Commercial
Style Name / Number	Get Moving Tile / 1T44
Construction	Tufted
Surface Appearance	Pattern Loop
Gauge	1/12" (47.00 rows per 10 cm)
Density	5,040
Dye Method	100% Solution Dyed
Fiber Type	Colorstrand® SD Nylon
Stain Release Technology	Mohawk Protection Plus Stain
Soil Release Technology	Mohawk Protection Plus Soil
Primary Backing	Non Woven Synthetic
Secondary Backing	UltraSet® Matrix
Indoor Air Quality	Green Label Plus Certified # 1171
NSF 140	Gold
Size	24" x 24" (.6096 m x .6096 m)
Yards Per Carton	8 sqyd/ctn
Installation Method	Quarter Turn / Brick Ashlar / Vertical Ashlar /
	Multi Directional / Monolithic
Flammability	ASTM E 648 Class 1 (Glue Down)
Smoke Density	ASTM E 662 Less than 450
Static Propensity	AATCC-134 Under 3.5 KV
Warranties	Lifetime Limited Wear Warranty
	Lifetime Limited Static Protection Warranty
	Lifetime Limited Edge Ravel, Zippering, Delamination,
	and Dimensional Stability Warranty
	Lifetime Limited Colorfastness to Light Warranty
	10 Year Limited Stain Resistance Warranty
	10 Year Limited Colorfastness to Atmospheric Contaminants

BrandStyle Name / Number	
Construction	
Surface Appearance	
Gauge	1/12" (47.00 rows per 10 cm)
Density	4.097
Dye Method	100% Solution Dyed
Fiber Type	Colorstrand® SD Nylon
Stain Release Technology	Mohawk Protection Plus Stain
Soil Release Technology	Mohawk Protection Plus Soil
Primary Backing	Non Woven Synthetic
Secondary Backing	UltraSet® Matrix
Indoor Air Quality	
NSF 140	Gold
Size	
Yards Per Carton	(
Installation Method	Ouarter Turn / Brick Ashlar / Vertical Ashlar /
motalidation would a	Multi Directional / Monolithic
Flammability	
Smoke Density	
Static Propensity	
Warranties	Lifetime Limited Wear Warranty
**arrantioo	Lifetime Limited Static Protection Warranty
	Lifetime Limited Edge Ravel, Zippering, Delamination,
	and Dimensional Stability Warranty
	Lifetime Limited Colorfastness to Light Warranty
	10 Year Limited Stain Resistance Warranty
	10 Year Limited Colorfastness to Atmospheric Contaminants
	To Tour Elimitor obioridoridos to Autiosphiblic dontaminanto



Installation Instructions:

CARPET TILE

Monolithic	Quarter Turn	Brick Ashlar	Vertical Ashlar	Multi-Directiona
† † †	↑ → ↑	† † †	T 1	↑ ↓ ←
† † †	\rightarrow \uparrow \rightarrow	↑ ↑ ↑	1 1	→ ↑ →
1 1 1 1 1 I	↑	↑ ↑ ↑	1 1	← → ↓

Printed on FSC* certified paper



Mohawk Industries, Inc. warrants its adhesives for the life of the original installation only when a Mohawk Industries style (product) is installed. Mohawk's floor preparation procedures must be followed to ensure that the substrate has been prepared properly. The use of Mohawk branded adhesives is required to ensure optimum results and are the only approved adhesives warranted by Mohawk. Please contact your local Sales Representative for installation guidelines.

Mohawk is providing this architect folder for the purpose of promoting our commercial business. Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations or other factors. The performance of this product is not affected by such variations. We recommend the use of chair pads on all commercial installations.

For current and complete specifications please call tech support at 888-387-9881 or visit www.AladdinCommercial.com I 800.233.4490



