

## Mohawk Group

## Hand Tufted Rug – HT650

	Metric	Imperial	
Weave Type	Hand Tufted		
Pile Yarn (BS 3655)	100% Pure Wool (New Zealand Origin – Cut Pile)		
Yarn Count	R380/1	1/82	
Number of Ends / Insertions	4		
Backing Materials	Secondary Backing – C	Primary Backing – Cotton 67% / Polyester 33% Secondary Backing – Cotton, Natural Latex With Fire Retardant Compound.	
Gauge	23 ends/dm	5.8 per inch	
Rows	22 ends/dm	5.6 per inch	
Tuft Density	506 per sq dm	32 per sq inch	
Total Pile Height ISO 1766 (BS 4223)	12.5mm	0.49″	
Total Rug Thickness ISO 1765 (BS 4051)	14- 15mm	0.55 - 0.59″	
Total Pile Weight ISO 8543 (BS 4223)	3525g per sq m	103.95 oz per sq yd	
Total Carpet Weight ISO 8543 (BS 4223)	4710g per sq m	138.90 oz per sq yd	
	Skein dyeing with pre-me	tallised complex dyes	

DYEING METHOD		Skein dyeing with pre-metallised complex dyes.	
COLOUR FASTNESS TO	SHAMPOOING	- BS 1006	Minimum 4 – 5
	RUBBING	- BS EN ISO 105-X12 (BS 1006)	Minimum 4 – 5

## **Qualifications to Specification**

1. There may be slight variation between the actual product and the specification.

2. The figures quoted are for PLAIN COLOURED CARPETS IN CUT PILE ONLY.

3. Carpets with intricate designs or using different construction methods shall have considerable differences.