


# Carpet Tile A

## Overview

Feature	Description
Collection	Shape Theory
Style	Cartesian Plane (BT600)
Product Type	Carpet Tile
Size	24" X 24"
Construction	Tufted
Surface Appearance	Textured Patterned Multi-Colored Loop
Fiber	ColorStrand® Nylon
Dye Method	Solution Dyed
Stain Release Technology	EcoSentry Plus Stain Protection
Soil Release Technology	EcoSentry Soil Protection
Backing	EcoFlex Matrix
Pile Weight	16.00 oz/yd <sup>2</sup> (543 g/m <sup>2</sup> )
Gauge	1/12 (47.00 rows per 10 cm)
Stitches per Inch	11.5 (45.28 per 10cm)
Total Thickness	0.200" (5.08 mm)
Density	6400
Installation	FlexLok, Glue Down
Installation Method	Quarter Turn, Monolithic, Vertical Ashlar, Brick Ashlar, Multi-Directional
Recommended Adhesive	Enpress, M700 Plus, FlexLok+ Tabs, Total Bond




## Recommended Installation Methods




Quarter Turn




Monolithic



Vertical Ashlar



Brick Ashlar



Multi-Directional

## Colorways



### Iron Index

Color code: 977  
Style number: BT600

## Testing

Feature	Description
TARR Rating	Heavy Traffic
Flammability	(ASTM E 648) Class 1 Glue Down
Static Propensity	(AATCC-134) < 3.5 KV
Smoke Density	(ASTM E 662) < 450

## Sustainability

Feature	Description
Embodied Carbon	7.19 kg CO2e/sq m2
Carbon Handprint	-7.55 kg CO2e/sq m2
Beyond Carbon Neutral	-0.36
Pre-Consumer Recycled Content	44%
HPD	EcoFlex Matrix HPD
NSF 140	<a href="#">EcoFlex Matrix - NSF 140 Gold</a>
Indoor Air Quality	GLP 1171
Mindful Materials	Participates
End of Life	ReCover

## Packaging

Feature	Description
Square Yards Per Carton	10.67
Cartons Per Pallet	22
Weight Per Carton	37.92

## Warranties

Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static