



Ecoflex™ Echo / Animate


Carpet Tiles

Technical Specifications

Spécifications techniques - Technische specificaties - Technische Spezifikationen

Construction Structure - Structuur - Konstruktion		Tufted 1/12" gauge loop
Pile fibre composition Composition des fibres - Poolmateriaal - Material der Polnutzschicht		100% SDN Thrive® Matter (90% recycled content)
Secondary backing Envers - Rug - Beschichtung		Ecoflex™ Echo (94% recycled PES Felt)
Total weight Poids total - Totaal gewicht - Gesamtgewicht		+/- 4750 g/m ²
Pile weight Poids du velours - Poolgewicht - Poleinsatzgewicht		+/- 700 g/m ²
Surface pile weight Poids du velours utile - Effectieve poolmassa - Polnutzschichtgewicht		+/- 433 g/m ²
Total thickness Epaisseur totale - Totale dikte - Gesamtdicke		+/- 8,8 mm
Surface pile thickness Hauteur du velours - Poolhoogte - Poldicke		+/- 3,3 mm
Surface pile density Densité du velours - Pooldichtheid - Polrohdichte		+/- 0,132 g/cm ³
Number of tufts Nombre de boucles - Aantal noppen - Noppenzahl		234.600/m ²
Wear classification Classement d'usage - Gebruiksklasse - Beanspruchungsklasse	EN 1307	33 / LC2
Castor chair suitability Résistance aux chaises à roulettes - Rolstoelgeschiktheid - Stuhlrolleneignung	EN 985	A: intensive use
Fire classification Comportement au feu - Brandgedrag - Brandklasse	EN 13501-1	Bfl-s1
Dimensional stability Stabilité dimensionnelle - Dimensionele stabiliteit - Dimensionsstabilität	EN 986	≤ 0,2%
Colour fastness to light Solidité des couleurs à la lumière - Lichtbestendigheid van de kleuren - Lichtechtheit	EN ISO 105-B02	≥ 7
Rubbing fastness Solidité au frottement - Wrijftechtheid - Reibechtheit	EN ISO 105-X12	≥ 4
Colour fastness to water Solidité à l'eau - Waterechtheid - Wasserechtheit	EN ISO 105-E01	≥ 4
Thermal resistance Résistance thermique - Warmtedoorlaatweerstand - Wärmedurchlasswiderstand	ISO 8302	0,123 m ² .K/W
Sound absorption Absorption phonique - Geluidsabsorptie - Schallabsorptionsgrad	EN ISO 354	0,30 aw Hz 125 250 500 1000 2000 4000 as 0,00 0,03 0,32 0,23 0,33 0,50
Impact sound reduction Réduction phonique aux bruits d'impacts - Reductie contactgeluid - Trittschallverbesserungsmaß	EN ISO 10140-3	ΔLw = 29 dB
Permanent antistatic Antistatique permanent - Permanent antistatisch - Permanent antistatisch	ISO 6356	≤ 2 kV
Number of colours Nombre de coloris - Aantal kleuren - Anzahl der Farben		18
Size & Packaging Dimensions & Emballage - Formaat en verpakking - Abmessungen & Verpackung		50 x 50 cm 4,5 m ² /box - 24 boxes/pallet
GUT-Prodís Number Numéro GUT Prodís - Nummer GUT Prodís - GUT-Prodís Nummer		Ongoing

We reserve all rights for technical improvements. 08/2020





Colorways




Animate 140

Colour code: 140
Colour: Yellow



Animate 232

Colour code: 232
Colour: Orange rust



Animate 467

Colour code: 467
Colour: Purple



Animate 474

Colour code: 474
Colour: Purple



Animate 543

Colour code: 543
Colour: Blueteal




Animate 545

Colour code: 545
Colour: Blueteal



Animate 559

Colour code: 559
Colour: Blueteal



Animate 569

Colour code: 569
Colour: Blueteal



Animate 574

Colour code: 574
Colour: Purple, Blueteal



Animate 621

Colour code: 621
Colour: Green



Animate 699

Colour code: 699
Colour: Green



Animate 731

Colour code: 731
Colour: Beige



Animate 848

Colour code: 848
Colour: Brown



Animate 904

Colour code: 9004
Colour: Grey, Beige



Animate 911

Colour code: 911
Colour: Grey



Animate 969

Colour code: 969
Colour: Grey



Animate 979

Colour code: 979
Colour: Grey



Animate 989

Colour code: 989
Colour: Grey, Black