




Ecoflex™ Echo / Tailored Carpet Tiles

Technical Specifications

Spécifications techniques - Technische specificaties - Technische Spezifikationen

Construction Structure - Structuur - Konstruktion		Tufted 1/12" gauge loop
Pile fibre composition Composition des fibres - Poolmateriaal - Material der Polnutzschicht		100% SDN Thrive® Matter (90% recycled content)
Secondary backing Envers - Rug - Beschichtung		Ecoflex™ Echo (94% recycled PES Felt)
Total weight Poids total - Totaal gewicht - Gesamtgewicht		+/- 4800 g/m ²
Pile weight Poids du velours - Poolgewicht - Poleinsatzgewicht		+/- 720 g/m ²
Surface pile weight Poids du velours utile - Effectieve poolmassa - Polnutzschichtgewicht		+/- 474 g/m ²
Total thickness Epaisseur totale - Totale dikte - Gesamtdicke		+/- 8,9 mm
Surface pile thickness Hauteur du velours - Poolhoogte - Poldicke		+/- 3,7 mm
Surface pile density Densité du velours - Pooldichtheid - Polrohdichte		+/- 0,128 g/cm ³
Number of tufts Nombre de boucles - Aantal noppen - Noppenzahl		230.000/m ²
Wear classification Classement d'usage - Gebruiksklasse - Beanspruchungsklasse	EN 1307	33 / LC2
Castor chair suitability Résistance aux chaises à roulettes - Rolstoelgeschiktheid - Stuhlrolleneignung	EN 985	A: intensive use
Fire classification Comportement au feu - Brandgedrag - Brandklasse	EN 13501-1	Bfl-s1
Dimensional stability Stabilité dimensionnelle - Dimensionele stabiliteit - Dimensionsstabilität	EN 986	≤ 0,2%
Colour fastness to light Solidité des couleurs à la lumière - Lichtbestendigheid van de kleuren - Lichtechtheit	EN ISO 105-B02	≥ 7
Rubbing fastness Solidité au frottement - Wrijftechtheid - Reibechtheit	EN ISO 105-X12	≥ 4
Colour fastness to water Solidité à l'eau - Waterrechtheid - Wasserechtheit	EN ISO 105-E01	≥ 4
Thermal resistance Résistance thermique - Warmtedoorlaatweerstand - Wärmedurchlasswiderstand	ISO 8302	0,121 m ² .KW
Sound absorption Absorption phonique - Geluidsabsorptie - Schallabsorptionsgrad	EN ISO 354	0,25 aw Hz 125 250 500 1000 2000 4000 as 0,00 0,03 0,31 0,21 0,31 0,48
Impact sound reduction Réduction phonique aux bruits d'impacts - Reductie contactgeluid - Trittschallverbesserungsmaß	EN ISO 10140-3	ΔLw = 30 dB
Permanent antistatic Antistatique permanent - Permanent antistatisch - Permanent antistatisch	ISO 6356	≤ 2 kV
Number of colours Nombre de coloris - Aantal kleuren - Anzahl der Farben		16
Size & Packaging Dimensions & Emballage - Formaat en verpakking - Abmessungen & Verpackung		50 x 50 cm 4 m ² /box - 24 boxes/pallet
GUT-Prodis Number Numéro GUT Prodis - Nummer GUT Prodis - GUT-Prodis Nummer		Ongoing

We reserve all rights for technical improvements. 11/2023





Colorways



Tailored 383

Colour code: 383
Colour: Orange rust



Tailored 419

Colour code: 419
Colour: Pink



Tailored 468

Colour code: 468
Colour: Purple



Tailored 542

Colour code: 542
Colour: Blueteal



Tailored 545

Colour code: 545
Colour: Blueteal



Tailored 559

Colour code: 559
Colour: Blueteal



Tailored 569

Colour code: 569
Colour: Blueteal



Tailored 627

Colour code: 627
Colour: Green



Tailored 656

Colour code: 656
Colour: Green



Tailored 731

Colour code: 731
Colour: Beige



Tailored 848

Colour code: 848
Colour: Brown



Tailored 904

Colour code: 904
Colour: Grey



Tailored 911

Colour code: 911
Colour: Grey



Tailored 969

Colour code: 969
Colour: Grey



Tailored 979

Colour code: 979
Colour: Grey



Tailored 989

Colour code: 989
Colour: Grey, Black