

Aquila DS Plus



TECHNICAL SPECIFICATIONS

Country of Origin:	Belgium	Units Per Box:	6
Colours:	8 Standard	m ² per box:	2.21
Total Product Thickness:	4.5mm	m ² per pallet:	119.34
Hard Flooring Size:	246mm x 1498mm	Finish:	Matte
Installation Method:	Direct Stick	Surface:	Embossed
Notes:	^ Subject to proper installation and maintenance. Not suitable for areas with floor drains or excessive moisture/flooding.	Profile:	Micro Bevel
Type:	Vinyl Plank Flooring	Protective Coating:	Superguard®
Wear Layer:	0.55mm		

PERFORMANCE

Flammability:	Direct Stick: (EN ISO 9239) CRF 8.6kW/m ² With Underlay: (EN ISO 9239) CRF 9.0kW/m ²
Colourfast to light:	(EN ISO 105-B02) ≥6
Light Reflectance:	100 Pearl - 66.11 180 Heather - 17.5 300 Topaz - 27.63 350 Totara - 22.19 500 Rose Gold - 49.53 520 Toi Toi - 34.77 550 Tussock - 28.25 580 Summit - 30.14 700 Limestone - 21.89 720 Titanium - 36.48 750 Paua - 20.7 780 Onyx - 26.58
Contract Guarantee:	Available on request*
Smoke Value:	Direct Stick: (EN ISO 9239) 217% minutes With Underlay: (EN ISO 9239) 367% minutes
Dimensional Stability:	(ISO 23999) Length: 0.05%, Width: 0.00%, Curling: 0.00%
Abrasion Rating:	(EN 660-2) Group T
Residual Indentation:	(ISO 24343-1) <0.1mm
Castor Chair:	(ISO 4918) No damage
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS 4586) P3, R9
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com

SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Product Transparency:	Global Green Tag, GreenRate Level A certified
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.



Green Building Council Australia
Member

Aquila DS Plus



100
PEARL



300
TOPAZ



350
TOTARA



520
TOI TOI



550
TUSSOK



700
LIMESTONE



720
TITANIUM



780
ONYX

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst vinyl plank products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Vinyl Plank Flooring Installation Instructions.

*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

^Subject to proper installation, maintenance and local building code/regulatory approval.