

Regent 1500



TECHNICAL SPECIFICATIONS

Country of Origin:	South Korea	Units Per Box:	10 boards
Colours:	12 Standard	m ² per box:	2.71
Total Product Thickness:	4.5mm	m ² per pallet:	162.6
Hard Flooring Size:	178mm x 1524mm	Finish:	Matte
Installation Method:	Direct Stick	Surface:	Embossed
Type:	Vinyl Plank Flooring	Profile:	Square Edge
Wear Layer:	0.5mm	Protective Coating:	PUR

PERFORMANCE

Flammability:	Direct Stick: (EN ISO 9239) CRF 7.2kW/m ² With Underlay: (EN ISO 9239) CRF 8.8kW/m ²
Colourfast to light:	(EN ISO 105-B02) 6-7
Light Reflectance:	105 - 42.44 180 - 11.05 300 - 22.14 350 - 13.58 380 - 13.05 545 - 19.96 550 - 14.12 555 - 16.23 560 - 19.50 700 - 39.08 740 - 25.84 790 - 13.49
Contract Guarantee:	Available on request*
Smoke Value:	Direct Stick: (EN ISO 9239) 196% minutes With Underlay: (EN ISO 9239) 167% minutes
Dimensional Stability:	(ISO 23999) Length: 0.00%, Width: 0.00%, Curling 0.5%
Abrasion Rating:	(EN 660-2) Group T
Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet
Slip Resistance:	(AS/NZ 4586-2013) P2, R9
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com
Thermal Conductivity:	TBA

SUSTAINABILITY

Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Product Transparency:	Global Green Tag, GreenRate Level A certified, Best Environmental Practice PVC certified product
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.



Green Building Council Australia Member



Regent 1500



105
EMMET



180
LONGREACH




300
BROKEN HILL



350
COBAR



380
BIRDSVILLE




545
GEORGETOWN



550
MELROSE



555
CHARLEVILLE



560
BURKE



700
SILVERTON



740
WINTON



790
STAMFORD

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All Godfrey Hirst vinyl plank products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Vinyl Plank Flooring Installation Instructions.

*Terms and conditions apply to all commercial warranties - contact your GH Commercial Account Manager.

^Subject to proper installation, maintenance and local building code/regulatory approval.