

Secoya 2.5 \$\$

Overview

Feature	Description
Collection	Hot and Heavy II
Style	Secoya 2.5 (C2103)
Product Type	LVT
Size	7" X 48"
Construction	Flexible LVT
Total Thickness	2.5 mm
Wear Layer	20 mil (0.5 mm)
Finish	M-Force Ultra
Surface Profile	Embossed
Edge Profile	Micro-Beveled
Installation	Glue Down
Installation Method	Monolithic, Brick Ashlar, Vertical Ashlar, Random
Recommended Adhesive	M95.0, M99, MS160, M700 Plus, or Total Bond Adhesive



Recommended Installation Methods



Monolithic



Brick Ashlar



Random

Colorways



Caramel Oak

Color code: 142
Style number: C2103



Knotty Oak

Color code: 148
Style number: C2103



Honey Maple

Color code: 828
Style number: C2103



Toffee Oak

Color code: 838
Style number: C2103



Amber Maple

Color code: 842
Style number: C2103



Hazelnut Oak

Color code: 848
Style number: C2103

Testing

Feature	Description
Squareness	(ASTM F2421) Passes
Size and Tolerance	(ASTM F2421) Passes
Thickness	(ASTM F386) Passes
Flexibility	(ASTM F137) Passes
Dimensional Stability	(ASTM F2199) Passes
Static Load Limit	(ASTM F970) 1000 psi
Residual Indentation	(ASTM F1914) Passes
Resistance to Chemicals	(ASTM F925) Passes
Resistance to Light	(ASTM F1515) Passes
Resistance to Heat	(ASTM F1514) Passes
Radiant Flux	(ASTM E648) Class 1
Smoke Density	(ASTM E662) 450
Wear Layer Thickness	20 mil (0.5 mm)
Lightfastness	(ASTM F1515) Passes

Sustainability

Feature	Description
Mindful Materials	Achiever

Packaging

Feature	Description
Pieces per Carton	18
Weight per Piece	2.0
Cartons Per Pallet	60
Square Feet per Carton	41.99
Weight per Carton	36

Warranties

Limited 20 Year M-Force Ultra Commercial Warranty