



Mohawk M95.0

Technical Data Sheet (TDS)

Resilient Flooring Adhesive for Commercial Sheet and LVT

Mohawk M95.0 is a premium high strength adhesive for installing resilient sheet, tiles and plank over porous substrates. Mohawk M95.0 is a solvent free, water-based acrylic adhesive suggested for use in occupied buildings, as it is low in odor, and contains "zero"(calculated) VOC's.

Features & Benefits

95% RH Moisture Limits

Solvent Free, "Zero"
Calculated VOC

FloorScore® Certified/Meets
requirements for CA SEC
01350 IAQ

CRI Green Label Plus
Approved SCAQMD Rule
1168 Compliant

Environmentally Conscious
Biodegradable Packaging

Non-Staining Formula

MicroSept™ Antimicrobial
Protection

Made in the USA



FOR USE

Mohawk M95.0 may be used for installations over concrete substrates with up to 95% in-stu relative humidity per latest version of ASTM F2170 and pH between 8.0 and 10.0. The Interior air temperature and relative humidity must be maintained between 65° and 85° F and 40% - 60% RH, and the substrate temperature should be at least 5 degrees F higher than the dew point.

BEFORE USING, READ ALL INSTRUCTIONS OR CALL MOHAWK TECHNICAL SERVICES AT 1-800-387-9881 OPTION #3

SUBSTRATES

Sound and properly prepared concrete (above, on and below grade), APA approved wood subflooring, and existing clean resilient flooring (non-cushion). Substrates must be clean and dry, free of dust, dirt, paint, wax, existing adhesives or other contaminants including curing compounds that may interfere with the adhesive bond. Do not use chemically cleaned substrates.

INSTALLATIONS

Porous Substrates:

- Sheet flooring may be placed into adhesive after 10-20 minutes. Do not allow the adhesive to dry completely
- Plank and tile over porous substrates should be installed into adhesive after 10-20 minutes open time in order for the adhesive to develop enough body to control slippage during placement.

WARNING

DO NOT USE FANS POINTED DIRECTLY AT THE ADHESIVE TO SPEED UP DRYING

RECOMMENDED COVERAGE AND TROWEL

1/16" x 1/32" x 1/32" U-Notch (width, depth, spacing) for all installations. Coverage will be up to 220-260 sq. feet per gallon.

ADHESIVE WORKING TIME

Working time depends on humidity and temperature. Flooring must be installed while the adhesive is still wet. Do not allow the adhesive to dry before placing product.

TRAFFIC

Allow 24 hours before immediate traffic. Immediate cleaning is allowed with seamless flooring. For all other applications allow 24 hours for light damp mopping and 72 hours for wet cleaning.

CLEAN UP

Use a clean wet cloth to clean up adhesive while still wet. Dried adhesive may require the use of mineral spirits.

LIMITATIONS

Not for outdoor use. Not for below grade installations. Shelf life 1 year from date of manufacturer, in an unopened container. Store indoors at a temperature of 65-95°F. Cannot be used over substrates which have been chemically cleaned. A bond test MUST be performed. Do not allow product to freeze.

PRECAUTIONARY STATEMENTS

In case of eye contact, flush with water for 10-15 minutes. If irritation persists contact a physician. If prolonged skin contact causes irritation, wash with soap and water. If swallowed, consult a physician. Avoid release to the environment. Safety glasses and gloves are recommended if contact is expected. Dispose of in accordance with local, regional, national, international regulations as specified. Read SDS for detailed product information. SDS may be obtained by calling Mohawk Technical Services at 800.833.6954.

SHELF LIFE

2 years from date of manufacture in unopened, properly stored container. Avoid excessive heat or cold. Protect from freezing. Store indoors at a temperature of 65°-95°F. LEED v4 PROGRAM CREDITS (where applicable).

- IEQ Credit 2.1, 2.2: Low Emitting Materials
- VOC content is below that established by California SCAQMD Rule 1168.
- Compliant with CA Section 01350